

NEC SpectraView® 2090



- Highly innovative LCD monitor with A-TW-IPS TFT display
- ColorComp: Compensates variations in the white homogeneity and improves colour and brightness homogeneity at the press of a button
- GammaComp: hardware calibration with 12-bit LUT (look up table) for 36-bit colour control and gamma correction
- ambix³™ Technology - safety of investment with analog/digital interfaces (DVI-I, DVI-D, VGA) with up to 3 inputs simultaneously
- OmniColor™: sRGB and 6-axis-colour-control (RGBCMY, hue and saturation)
- Realtime clock with scheduler
- CableComp for best picture quality through automatic signal compensation of long cables and weak signals incl. Sync continuity detection
- Advanced NTAA (Advanced Non-Touch-Auto-Adjustment) provides stable and excellent picture quality
- L-shape front button technology for intuitive OSD control
- ErgoDesign®: Height adjustable stand (150 mm)
- TORO™ Design: Screen rotation 90° (portrait capability)
- Rapid Response technology 8 ms (grey-to-grey)
- Low power consumption for reduced Total Cost of Ownership (TCO)
- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- Detachable light protection hood (black, lined with photo velvet)
- SpectraView® Profiler Software features:
 L* (CIE-LAB L*colour gamut), Gamma or sRGB calibration; Iterative calibration process; Profile validation for quick check at any time; LUT-based 16-bit ICC-profiles (or Matrix profiles); support of multiple measurement devices; Manual White Point and Calibration Curve Editing; White and Black luminance adjustment (or contrast ratio); Check of ambient light conditions and Viewing Booth in relation to ISO 3664 & 12646; Chromatic Adaptation



NEC SpectraView® 2090

Panel Technology	A-TW-IPS TFT
Screen Size [inch/cm]	20.1/51.0
Pixel Pitch [mm]	0.255
Viewing Angle	178° horizontal / 178° vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	700:1
Brightness (typ.) [cd/m ²]	280
Response Time (typ.) [ms]	8 (grey-to-grey), 16 (9 white / black; 7 black / white)
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	31.5 - 91.1
Vertical Frequency [Hz]	50 - 85
Optimum Resolution	1600 x 1200 at 60 Hz
Other Resolutions	1280 x 1024; 1280 x 960; 1200 x 1600; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D; Digital/ Analog: 1 x DVI-I; Analog: 1 x D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Advanced User Menu; Auto Adjust; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Fine Adjust (analogue); Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Manager (OSM) lock-out; Sharpness; User Menu
Safety and Ergonomics	CE; TCO'03; TÜV ergonomics approved; TÜV GS; C-tick; GEEA/Energy Label; Energy Star; FCC Class B; PCT/Gost; UL/ C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; PCBC/B-mark; PSB; RoHS
Power Requirements on Mode [W]	50 (max.)
Power Requirements Power-saving Mode [W]	1
Power Supply	100-120 V/220-240 V; 0.68 A/0.29 A; integrated power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height Adjustable Stand [mm]	150
Dimensions (W x H x D) [mm]	439.2 x 415.5 - 565.5 x 247.3 (Landscape mode)
Screen Tilt [°]	-5 to +30
Swivel [°]	-170 to +170
Bezel Width [mm]	14.6 (left and right)
Cable Management	yes
Kensington Lock	yes
Weight [kg]	9.7
Specials	Adjustable power LED (colour and brightness); Advanced NTAA (Advanced Non-Touch- Auto-Adjustment); AmbiBright; ambix3™; Auto Black Level; Auto Brightness; Auto Contrast; AutoBright Technology; CableComp with Sync Continuity Detection; ColorComp; DDC-CI; Direct brightness and contrast; EcoModes; GammaComp (12-bit look up table and 12-bit gamma correction); L-shape Front Button Technology; NaViSet® and NaViSet® Administrator compatible; OmniColor™; Overdrive; Quick release stand and handle; Rapid Response Technology; RapidMotion; Realtime clock with scheduler (Power-On and Power-Off timer); SpectraView® Profiler Software; TileComp; TileMatrix; TORO™ Design
Audio Functions	Option: MultiSync® Soundbar 90
Colour Versions	Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-A - VGA, DVI-D - DVI-D; CD-ROM and manual for display; CD-ROM with SpectraView® Profiler Software and manual; Detachable black light protection hood including accessories; SpectraView® Certifier document
Warranty	3 years warranty including backlight



All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 03/2007